







SAKI NE REMOTE CONTROL



HYDRAULIC WINCH



ILD02

SKID-STEERING

TECHNICAL SPECIFICATIONS

DRIVE UNIT

Engine	Kawasaki FS691V
Performance	24 HP / 17,9kW Gross HP SAE J1940
Displacement	726 ccm
Fuel tank	16 I / 4,2 gal
Fuel	Unleaded petrol

DRIVE SYSTEM

Transmission	Hydrostatic	
Oil tank	9 / 2,4 gal	
Speed	0 – 8 kmh / 0 – 5 mph	
Drive	360°, 4-wheel drive	
Tire type	16 × 6,50–8	

CUTTING SYSTEM

Cutting width	123 cm / 48,5 in (4 blades)
Cutting height	9 - 14 cm / 7 - 12 cm / 3,5 - 5,5 in / 2,8 - 4,7 in
Clutch	Electromagnetic

PERFORMANCE

up to 7000 m²/h / 1,73 acres/h
3,5 l/hour / 0,95 gal/hour
55° / 143% *
164 × 143 × 92 cm / 65 × 56 × 36 in
387 kg / 853 lb

The **ILD02** is Spider's best selling model. Developed to handle extreme slopes, inaccessible areas, dangerous terrains, fine turf and extensive mowing on large areas, all in one setup. The patented drive system enhanced with a skid-steering option enables mowing in all directions and extreme climbing ability up to 55° / 143%*. Its unique steering system, light weight and low center of gravity, eliminate the risk of erosion on steep slopes.

CONTACT

DETAILS

The four-blade mowing mechanism ensures a perfect cut and can easily handle unmaintained areas.

Its productivity is comparable to that of heavy machinery or 15 workers using brush cutters at significantly lower operating costs.

More than 10 years of continuous product development has resulted in a highly reliable product which is very important to the professional user.



o Cent

OTHER MODELS

SPIDER CROSS LINER

* Official certification documentation available upon request.



slope-mower.com